

MAXSPORT TYRES SPECIFICATION SHEET FOR RALLY TYRES

Size	S/W	OD (mm)	RC (mm)		Size	S/W	OD (mm)
RB3					RB 4		
165/70-13	160	580	1825		165/70-13	155	560
175/70-13	170	590	1880		185/70-13	170	585
185/70-14	160	620	1985		185/70-14	170	620
175/70-15	180	620	1990		175/70-15	165	615
175/70-15	160	620	1990		185/60-13	165	540
165/65-14	150	570	1830		185/60-14	160	590
175/65-14	160	590	1870		185/55-15	165	590
185/65-15	180	620	1990		195/55-15	200	595
185/65-15	160	620	1990		195/50-15	195	570
195/65-15	190	630	2020				
205/60-15	205	630	2014		RB 5		
185/55-15	195	580	1885		185/60-13	165	540
205/55-16	200	625	2005		185/60-14	170	565
					185/55-15	170	565
RB 1					205/55-15	200	600
145/70-12	140	520	1655		205/50-16	210	600
165/13	145	595	1910		215/45-17	220	615
165/70-13	145	580	1830				
185/70-13	150	595	1920		HAKKA RALLY		
165/65-14	150	580	1825		145/10	120	500
185/65-15	155	595	1920				
185/65-15	160	630	2000				

S/W : Inflated sectional width

OD(mm) : Inflated overall diameter

RC(mm) : Inflated rolling circumference

ALL RALLY TYRES HAVE A REINFORCED SIDEWALL CONSTRUCTION AS S

		SYMBOL	KM/H	MPH
RC (mm)		Q	160	100
		R	170	105
1800		S	180	113
1865		T	190	118
1960		H	210	130
1955		V	240	150
1725		VR	>210	>130
1825		W	270	169
1820		Y	300	186
1860		ZR	>240	>150
1805				
1740				
1820				
1820				
1915				
1915				
1960				
1585				
STANDARD				